

K-tech Piston Kit Application List

Make	Model	Year	Year	Type	SSK Kit Part No	SSRK Kit Part No	FCV Part No	Compression Adj	Rebound Adj	Comments	Spring	Oil Level/Air gap
Aprilia	RS250	1998	2002	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	3 clicks out (std adj)	2 - 2.5 turns out	Remove steel adjuster needle	??-???	??mm
Aprilia	RSV1000 Tuono	2002	2005	Showa	20SSK-SHO-1	20SSRK-SHO-1	N/A	3 clicks out (std adj)	2 - 2.5 turns out	Remove steel adjuster needle	??-???	120mm Spring In
Aprilia	RSV 1000	1998	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	3 clicks out (std adj)	2 - 2.5 turns out	Remove 26.50mm from std needle. Use original comp assy bolt with hole	38-288-	120mm Spring In
Aprilia	RSV 1000 Factory	2004	2008	Ohlins	25SSK-R&T-AP	25SSRK-R&T-AP	KT07-011A	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Aprilia	RSV4 R	2010	2010	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	38-295-	120mm Spring In
Aprilia	RSV4 R APRC	2011	2015	Sachs	118-450-030-020		125-900-509	12 clicks out			38-265-	110mm
Aprilia	RSV4 R RR	2015	2016	Sachs	118-450-030-020		125-900-509	12 clicks out			38-265-	110mm
Aprilia	RSV4 Factory	2009	2010	Ohlins	25SSK-R&T-AP	25SSRK-R&T-AP	KT07-011A	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Aprilia	RSV4 Factory	2011	2015	Ohlins	25SSK-R&T-AP	25SSRK-R&T-AP	KT07-011A	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Aprilia	RSV4 RF	2015	2016	Ohlins	25SSK-R&T-AP	25SSRK-R&T-AP	KT07-011A	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
BMW	S1000RR	2010	2014	Sachs	120-012-030-020	121-012-030-020	Inc in piston kit	12 clicks out	5 clicks out	Remove standard adjuster needle	4128-205-	105mm
Ducati	748	1994	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Std Compression Adj	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	38-288-	120mm Spring In
Ducati	748 Biposto	1994	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Std Compression Adj	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	38-288-	120mm Spring In
Ducati	748R	1994	2003	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use standard rebound adjuster needle	37-240-	
Ducati	749	2004	2007	Showa	20SSK-SHO-3	20SSRK-SHO-3	Std Compression Adj	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	3724-300-	120mm Spring In
Ducati	749R	2004	2007	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260	
Ducati	848	2007	2009	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	12 - 15 clicks out	Remove steel adjuster needle	38-315	150mm Spring In
Ducati	848 Evo	2010	2013	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	12 - 15 clicks out	Remove steel adjuster needle	38-315	150mm Spring In
Ducati	916	1994	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Std Compression Adj	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Ducati	916 Biposto	1994	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	Std Compression Adj	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	38-288-	120mm Spring In
Ducati	916R	1999	1999	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Ducati	996	2000	2001	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	38-288-	120mm Spring In
Ducati	996 Bisposto	2000	2001	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	38-288-	120mm Spring In
Ducati	996R	2000	2001	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Ducati	998	2002	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	38-288-	120mm Spring In
Ducati	998 Biposto	2002	2003	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	38-288-	120mm Spring In
Ducati	998R	2002	2003	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Ducati	999	2004	2006	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	38-300-	120mm Spring In
Ducati	999R	2004	2006	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Ducati	1098	2007	2008	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-07	12 clicks out	12 - 15 clicks out	Remove steel adjuster needle	38-315-	140mm Spring In
Ducati	1098R	2007	2008	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Ducati	1198	2009	2011	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-07	12 clicks out	12 - 15 clicks out	Remove steel adjuster needle	38-315-	140mm Spring In
Ducati	1198R	2009	2011	Ohlins	25SSK-R&T	25SSRK-R&T	K-TECH0061	10 clicks out	14 clicks out	Use standard rebound adjuster needle	36-260-	
Ducati	M900 Monster	2001	2009	Showa	20SSK-SHO-13		N/A	6 clicks out	12 - 15 clicks out	Call for instructions !	???	120mm Spring In
Ducati	M900 Monster S4R	2001	2005	Showa	20SSK-SHO-13		N/A	6 clicks out	12 - 15 clicks out	Call for instructions !	???	120mm Spring In
Ducati	ST4	2004	2005	Showa	20SSK-SHO-13		N/A	6 clicks out	12 - 15 clicks out	Call for instructions !	???	120mm Spring In
Ducati	1000DS Multistrada	2003	2006	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	6 clicks out	12 - 15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole	???	120mm Spring In
Ducati	M1100S Monster Evo	2007	2013	Marzocchi	118-250-026-001		125-900-510	6 clicks out	12 - 15 clicks out		3822-330-	???

K-tech Piston Kit Application List

Make	Model	Year	Year	Type	SSK Kit Part No	SSRK Kit Part No	FCV Part No	Compression Adj	Rebound Adj	Comments	Spring	Oil Level/Air gap
Honda	RS125R	1997	2011	Showa	20SSK-SHO-4-12		20K-FCV-SHO-1	12 clicks out	12-15 clicks out	Use standard adjuster rod	30-205-	95mm
Honda	NSF250R	2012	2016	Showa	20SSK-SHO-412		20K-FCV-SHO-1	12 clicks out	12-15 clicks out	Use standard adjuster rod	30-205-	95mm
Honda	VFR400 NC30	1988	1994	Showa	20SSK-SHO-NC30		N/A	N/A	1 - 2.5 turns out	Use Piston Rod & Adj Rod supplied		160mm
Honda	CBR600 F3	1997	2002	Showa	20SSK-SHO-7		N/A	N/A	2 - 2.5 turns out	Remove steel adjuster needle	35-375-	160mm
Honda	CBR600 F4	1999	2000	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3624-336-	145mm
Honda	CBR600 F4i	2001	2002	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3624-285-	145mm
Honda	CBR600RR	2003	2004	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	4026-250-	115mm
Honda	CBR600RR	2005	2006	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of needle	3624-270-	115mm
Honda	CBR600RR	2007	2012	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-07	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of needle	3624-245-	115mm
Honda	CBR900RR	1998	1999	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	4026-250-	115mm
Honda	CBR900RR 929	2000	2001	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3824-230-	100mm
Honda	CBR900RR 954	2002	2003	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3824-250-	100mm
Honda	CB1000R	2008	2016	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of needle	3824-250-	115mm
Honda	CBR1000RR	2004	2007	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of needle	3824-230-	100mm
Honda	CBR1000RR	2008	2011	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-07	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of needle	3824-235-	100mm
Honda	CRF1000L Africa Twin	2016-		Showa	118-500-020-016	N/A	N/A	N/A	2 - 2.5 turns out	Remove steel adjuster needle	40-445-	95mm
Honda	VTR1000 SP1	2000	2001	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	8 clicks out	2 - 2.5 turns out	Remove steel adjuster needle. Use original compression adj assembly.	3824-265-	110mm
Honda	VTR1000 SP2	2002	2005	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	8 clicks out	2 - 2.5 turns out	Remove steel adjuster needle. Use original compression adj assembly.	3824-265-	110mm
Honda	RCS1	2000	2005	Showa	20SSK-SHO-3	20SSRK-SHO-3	N/A	8 clicks out	2 - 2.5 turns out	Remove steel adjuster needle. Use original compression adj assembly.	3824-265-	110mm
Honda	VTR1000F	1997	2002	Showa	20SSK-SHO-7	N/A	N/A	N/A	2 - 2.5 turns out	Remove steel adjuster needle	35-315-	160mm
Honda	VFR1200F	2010	2016	KYB	20SSK-KYB-10	N/A	N/A	N/A	8-10- Clicks	Use standard adjuster rod	3824-250-	150mm
Honda	VFR1200X	2010	2016	KYB	20SSK-KYB-10	N/A	N/A	N/A	8-10- Clicks	Use standard adjuster rod	3824-340-	150mm
Kawasaki	ZRX400	1992	????	Showa	20SSK-SHO-ZXR4	N/A	N/A	N/A	2.5 turns out	Use Piston Rod & Adj Rod supplied	35-315-	120mm
Kawasaki	ZX-6R	1998	1999	KYB	20SSK-KYB-7		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	4026-270-	115mm
Kawasaki	ZX-6R	2000	2002	KYB	20SSK-KYB-7		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	4026-245-	115mm
Kawasaki	ZX-6R	2003	2004	KYB	20SSK-KYB-5		20K-FCV-SHO-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 1.50mm	3624-250-	115mm
Kawasaki	ZX-6R 636	2003	2004	KYB	20SSK-KYB-5		20K-FCV-SHO-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 1.50mm	3624-250-	115mm
Kawasaki	ZX-6RR	2005	2006	Showa	20SSK-SHO-6	20SSRK-SHO-6	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3624-295-	115mm
Kawasaki	ZX6-R 636	2005	2006	Showa	20SSK-SHO-5-12	20SSRK-SHO-5-12	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3624-250-	115mm
Kawasaki	Z900	2017		KYB	118-200-020-012	N/A	N/A	N/A	2-2.5 Turns out	Shorten adjuster rod 1.50mm	3624-285-	115mm
Kawasaki	Z900RS	2018		KYB	118-200-020-015	N/A	125-900-514	N/A	2-2.5 Turns out	Shorten adjuster rod 5.00mm	3624-285-	125mm
Kawasaki	ZX-9R	1998	1999	KYB	20SSK-KYB-7		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	4026-270-	115mm
Kawasaki	ZX-9R	2000	2003	KYB	20SSK-KYB-7		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	4026-245-	115mm
Kawasaki	Z1000	2007	2009	Showa	20SSK-SHO-7		N/A	2 - 2.5 turns out	2 - 2.5 turns out		3624-270-	115mm
Kawasaki	Z1000SX	2014	2016	Showa	???-???-???-???		20K-FCV-SHO-7	(one leg)			35-315-	115mm
Kawasaki	ZX-10R	2004	2005	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 1.50mm	3824-240-	100mm
Kawasaki	ZX-10R	2006	2007	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 1.50mm	3824-230-	100mm
Kawasaki	ZX-10R	2008	2010	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 1.50mm	38-235-	100mm
Kawasaki	ZRX1100	1997	2001	KYB	20SSK-INT-KYB-1		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	3724-330-	125mm
Kawasaki	ZX1400	2007	2016	KYB	20SSK-INT-KYB-3	20SSRK-KYB-3	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out		3824-250-	
Kawasaki	ZZR1400	2007	2016	KYB	20SSK-INT-KYB-3	20SSRK-KYB-3	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out		3824-250-	

K-tech Piston Kit Application List

Make	Model	Year	Year	Type	SSK Kit Part No	SSRK Kit Part No	FCV Part No	Compression Adj	Rebound Adj	Comments	Spring	Oil Level/Air gap
MV Agusta	F4 750	2003	2006	Showa	20SSK-SHO-3	20SSRK-SHO-3	20K-FCV-SHO-1	12 clicks out	12-15 clicks out	Remove steel adjuster needle. Use original comp assy bolt with hole		120mm
Suzuki	GSX-R600	1998	2000	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	4026-270-	115mm
Suzuki	GSX-R600	2000	2003	Showa	20SSK-SHO-1	20SSRK-SHO-2	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	4026-245-	115mm
Suzuki	GSX-R600	2004	2005	Showa	20SSK-SHO-5	20SSRK-SHO-5	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of needle	3824-240-	100mm
Suzuki	GSX-R600	2006	2007	Showa	20SSK-SHO-512	20SSRK-SHO-5-12	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3624-270-	115mm
Suzuki	GSX-R600	2008	2010	Showa	20SSK-SHO-512	20SSRK-SHO-5-12	20K-FCV-SHO-07	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3624-270-	115mm
Suzuki	GSX-R750	2000	2003	Showa	20SSK-SHO-2		20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3824-250-	110mm
Suzuki	GSX-R750	2004	2005	Showa	20SSK-SHO-5	20SSRK-SHO-5	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 28.50mm from tip of needle	3824-240-	100mm
Suzuki	GSX-R750	2006	2007	Showa	20SSK-SHO-5-12	20SSRK-SHO-5-12	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove steel adjuster needle	3624-270-	115mm
Suzuki	GSX-R750	2008	2010	Showa	20SSK-SHO-15	20SSRK-SHO-15	N/A	LS:13 out HS:2 1/2 turns	2 - 2.5 turns out	Remove steel adjuster needle	3624-270-	115mm
Suzuki	GSX-R1000	2001	2002	KYB	20SSK-KYB-2	20SSRK-KYB-2	20K-FCV-KYB-2	12 clicks out	8 - 10 clicks out	Use standard adjuster rod	3824-230-	100mm
Suzuki	GSX-R1000	2003	2004	KYB	20SSK-KYB-3	20SSRK-KYB-3	20K-FCV-KYB-2	12 clicks out	8 - 10 clicks out	Use standard adjuster rod	3824-230-	100mm
Suzuki	GSX-R1000	2005	2006	KYB	20SSK-KYB-3	20SSRK-KYB-3	20K-FCV-KYB-2	12 clicks out	8 - 10 clicks out	Use standard adjuster rod	3824-230-	100mm
Suzuki	GSX-R1000	2007	2008	KYB	20SSK-KYB-9	20SSRK-KYB-9	Inc in piston kit	LS:13 out HS:3 turns	8 - 10 clicks out	Use standard adjuster rod	3824-240-	100mm
Suzuki	GSX-S1000	2015		KYB	118-200-020-013		20K-FCV-KYB-3			Use standard adjuster rod	3824-270-	110mm
Suzuki	TL1000S	1997	2001	KYB	120-008-230-025		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Use standard adjuster rod		100mm
Suzuki	TL1000R	1998	2003	KYB	120-008-230-025		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Use standard adjuster rod	3824-250-	100mm
Suzuki	GSX1300R Hayabusa	1999	2007	KYB	120-008-230-025		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Use standard adjuster rod	3824-250-	100mm
Suzuki	GSX1300R Hayabusa	2008	2016	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Use standard adjuster rod	3827-265-	100mm
Suzuki	B-King 1300	2006	2016	KYB	20SSK-KYB-1A		20K-FCV-KYB-2	12 clicks out	2 - 2.5 turns out	Use standard adjuster rod	3824-265-	100mm
Triumph	Daytona 600	2002	2004	KYB	20SSK-KYB-4		20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten adj rod 1.50mm	3624-245-	115mm
Triumph	Daytona 675	2006	2008	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten adj rod 1.50mm	3624-245-	115mm
Triumph	Daytona 675	2009	2012	KYB	20SSK-KYB-9	20SSRK-KYB-9	Inc in piston kit	LS:13 out HS:3 turns	8 - 10 clicks out	Use standard adjuster rod	3624-235-	115mm
Triumph	Street Triple 675R	2008	2012	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten adj rod 1.50mm	3624-245-	115mm
Triumph	Daytona T509	1997	1998	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 26.50mm from tip of needle	4026-245-	110mm
Triumph	Daytona T595	1997	1998	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 26.50mm from tip of needle	4026-245-	110mm
Triumph	Daytona 955i	1997	2006	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-1	12 clicks out	2 - 2.5 turns out	Remove 26.50mm from tip of needle	4026-245-	110mm
Triumph	Speed Triple 1050	2005	2010	Showa	20SSK-SHO-11		N/A	1.5 turns out	1.5 turns out	Remove 24.00mm from tip of needle	38-288-	150mm Spring In
Triumph	Speed Triple 1050	2011	2015	Showa	20SSK-SHO-1	20SSRK-SHO-1	20K-FCV-SHO-07	12 clicks out	2 - 2.5 turns out	Remove 24.00mm from tip of needle	38-288-	150mm Spring In
Triumph	Tiger 1050	2007	2011	Showa	20SSK-SHO-9		N/A	1.5 turns out	1.5 turns out	Remove 24.00mm from tip of needle	38-288-	100mm Spring In
Yamaha	YZF-R6	1998	2000	KYB	20SSK-KYB-4		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	3624-250-	145mm
Yamaha	YZF-R6	2001	2002	KYB	20SSK-KYB-4		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	37-240-	145mm
Yamaha	YZF-R6	2003	2004	KYB	20SSK-KYB-4		20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	37-240-	145mm
Yamaha	YZF-R6	2005	2005	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 1.50mm	3624-245-	110mm
Yamaha	YZF-R6	2006	2007	Soqi	20SSK-KYB-4-HL	20SSRK-KYB-4-HL	N/A	LS:10 out HS:2.5 turns	10 - 14 clicks out	Remove std nut from piston rod	3624-245-	115mm
Yamaha	YZF-R6	2008	2015	Soqi	20SSK-KYB-4-HL	20SSRK-KYB-4-HL	N/A	LS:10 out HS:2.5 turns	24 - 30 clicks out	Remove std nut from piston rod	3624-250-	115mm
Yamaha	YZF-R6	2016	2016	KYB	20SSK-KYB-9	20SSRK-KYB-9	N/A	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 1.50mm	3624-270-	115mm
Yamaha	YZF-750R	1993	1997	KYB	20SSK-KYB-1	20SSRK-KYB-1	20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	3624-336-	110mm
Yamaha	FZ-09	2014	2016	KYB	118-200-020-012	N/A	N/A	N/A		Shorten adjuster rod 1.50mm	3624-300-	125mm
Yamaha	FZ-09	2017		KYB	118-200-020-014	N/A	N/A	N/A		Shorten adjuster rod 1.50mm	3624-300-	125mm
Yamaha	MT-09	2014	2016	KYB	118-200-020-012	N/A	N/A	N/A		Shorten adjuster rod 1.50mm	3624-300-	125mm
Yamaha	MT-09	2017		KYB	118-200-020-014	N/A	N/A	N/A		Shorten adjuster rod 1.50mm	3624-300-	125mm
Yamaha	MT-09 SP	2018		KYB	20SSK-KYB-9	20SSRK-KYB-9	Inc in piston kit	LS:13 out HS:3 turns	8 - 10 clicks out	Use standard adjuster rod	3624-235-	125mm
Yamaha	YZF-R1	1998	2001	KYB	20SSK-KYB-1	20SSRK-KYB-1	20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	3624-250-	110mm
Yamaha	YZF-R1	2002	2003	KYB	20SSK-KYB-1	20SSRK-KYB-1	20K-FCV-KYB-1	12 clicks out	8 - 10 clicks out	Shorten adjuster rod 20.00mm	3824-250-	100mm
Yamaha	YZF-R1	2004	2006	KYB	20SSK-KYB-1A	20SSRK-KYB-1A	20K-FCV-KYB-3	12 clicks out	16-20 clicks out	Shorten adjuster rod 20.00mm	3824-230-	100mm
Yamaha	YZF-R1	2007	2008	KYB	24SSK-KYB-1	20SSRK-KYB-1	20K-FCV-KYB-3	12 clicks out	16-20 clicks out	Use standard adjuster rod	3824-230-	100mm
Yamaha	FZS1000 Fazer	2001	2005	Soqi	20SSK-KYB-8	N/A	N/A	8-10 clicks out	20-24 clicks out	Shorten adjuster rod 20.00mm	3624-336-	130mm
Yamaha	FZ1	2006	2015	Soqi	118-200-020-011	N/A	N/A	16 clicks out	20 clicks out	Shorten adjuster rod 4.50mm	3824-250-	120mm
Yamaha	FJR1300	2001	2015	Soqi	20SSK-KYB-8	N/A	N/A	8-10 clicks out	20-24 clicks out	Shorten adjuster rod 20.00mm		